

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **08240294 A**

(43) Date of publication of application: **17.09.96**

(51) Int. Cl.

F16L 47/02
B29C 65/34
F16L 41/02
// B29L 23:00
B29L 31:24

(21) Application number: **07045718**

(71) Applicant: **MITSUBISHI PLASTICS IND LTD**

(22) Date of filing: **06.03.95**

(72) Inventor: **NAKAMURA RYUICHIRO**

(54) BRANCHED JOINT FOR ELECTRICALLY FUSED CONNECTION

(57) Abstract:

PURPOSE:—To provide a branched pipe joint for an electrically fused connection, ensuring the rear side of a saddle to be firmly fused and jointed to the external surface of a main pipe for preventing a fluid in the pipe to ooze or leak.

CONSTITUTION: Annular grooves 13a and 13b are formed on the inner or outer peripheral position of the reverse side of a saddle 11 having an electrical heating wire 2 buried, and seal packings 3 are coupled to the annular grooves 13a and 13b. As a result, the reverse side of the saddle 11 and the external surface of a main pipe are firmly fused and jointed to each other, thereby ensuring a fluid in the pipe to be prevented from oozing or leaking.

COPYRIGHT: (C)1996,JPO

